hohem

iSteady M6



User Manual V2.0

EN	01 - 24	User Manual
JP	25 - 48	ユーザーマニュアル
KR	49 - 72	사용자 매뉴얼
DE	73 - 97	Benutzerhandbuch
IT	98 - 122	Manuale d'uso
FR	123 - 147	Manuel de l'utilisateur
ES	148 - 171	Manual del usuario
RU	173 - 196	Руководство пользователя

Contents

01 Product List 1
02 Get to Know iSteady M6 2
03 Battery and Charging 3
04 Download the App Hohem Joy 4
05 Mounting, Balancing and Powering on 5
Mounting the Phone 5
Balancing the Phone 6
Powering on & Standby 8
Installing Magnetic AI Vision Sensor 8
06 How to Enable the AI Tracking 9
07 How to Use the Gimbal 11
On-board Features 11
Modes Description 14
Manual Tilt Adjustment 15
08 OLED Display 15
09 How to Use the APP 17
How to Connect 17
APP Features 18
10 Auto Calibration and Firmware Update 19
Calibration Reasons and How to Calibrate 19
Firmware Update 20
11 Specifications 21
12 Disclaimer 22
13 Warranty Terms 23
Warranty Terms 23
Warranty Card 24

01 Product List



iSteady M6

Fill Light with AI Vision Sensor

* Sold separately

Tripod



Carrying Case



USB-C Charging Cable

USB-C to USB-C Cable

User Manual

02 Get to Know iSteady M6





1. Magnetic Fill Light with AI Vision Sensor * Sold separately
2. Magnetic Alignment
3. Phone Clamp
4. 1/4"-20 UNC Port*
5. Roll Axis Lock Pin
6. Pan Motor
7. Multifunctional Control Wheel
8. Buttons for A-B Motion
9. Joystick
10. Handle
11. Tripod
12. Tilt Motor
13. OLED Display
14. M (Mode) Button
15. Zoom Lever
16. Shutter Button
17. DC out Port for Phones
18. Roll Axis Arm
19. USB-C Charging Port
20. Power Button
21. 1/4"-20 UNC Port*
22. Clamp Rotation Axis
23. Roll Axis Arm Latch
24. Roll Motor
25. Pan Axis Latch
26. Trigger

*Depth: 5.9mm

03 Battery and Charging

Please fully charge the iSteady M6 before using it **for the first time**.

Charging Method: To charge the iSteady M6, connect a USB adapter (not included, choose 5V-2A for better results) into the charging port with the provided USB-C charging cable.



Charging Display: The battery is fully charged when the battery levels reach the highest point as shown on the OLED display.

Reverse Charging (DC out charging for smartphones)

Android: Charging with the provided USB-C to USB-C cable.
iOS: Charging with USB-C to Lightning cable (Not Included).



Tips:
When the gimbal is powered off, press the power button once to start charging your smartphone.

04 Download the App Hohem Joy

Scan the QR code or search "Hohem Joy" in APP Store or Google Play to download.

* The app Hohem Joy requires iOS 10.0 or later, Android 6.0 or later.

○ Items marked "*" are optional accessories which are sold separately.
○ Mount your mobile phone before powering on the iSteady M6.
○ If no mobile phone is detected or the motor is overloaded because the phone is not balanced well, the gimbal will shut down after a warning beeping.

05 Mounting, Balancing and Powering on

Mounting the Phone

❶

Unlock the roll axis and pan axis to ensure movable arms.



❷

Mounting in Landscape Mode: Make sure the camera direction is the same as shown in the image below and keep the phone clinging to the rubber pads.



❸

Mounting in Portrait Mode: Rotate the clamp by 90° to the right as shown in the image below and make sure it is in the middle of the mobile phone.





Balancing the Phone

❶

Unlock the roll axis arm latch and push the arm to the left or right until the phone is steady and almost at level with the ground. Then tighten the latch.



❷

For balancing in the portrait mode, keep the phone balanced centrally in the phone clamp.



Quick Switch to Portrait Mode

Switch to portrait mode by rotating the handle as shown in the image below and then hold the gimbal like a flashlight.

* After switching to portrait mode in this way, the joystick will only allow your camera to move left or right. Note that the gimbal should be held horizontally when in quick portrait mode; It is not available in POV mode.



Powering On & Standby



1. Press and hold for 3 seconds - Power on/off
2. When Powered On
   Press twice: Enter the standby mode
   Press once: Wake up the gimbal
3. Ultra-Wide-Angle Shot
   Default mode as shown in the image 1: There's no obstruction in front of phone screen.
   Ultra-wide-angle shot mode as shown in the image 2: Switch to this mode by **pressing trigger four times** and the roll motor will be in front of phone screen for capturing unobstructed views.



Installing Magnetic AI Vision Sensor * Sold separately



06 How to Enable the AI Tracking

* AI vision sensor sold separately

1. Enable the AI vision sensor: Switch to "ON".
   (Indicator light turns red with fill light flashing twice.)



2. Gesture Control: Show gestures to the AI vision sensor from 0.5~1.5m (1.64ft-4.92ft) away.



3. Gesture "" to start the AI tracking (Indicator light turns green).
4. Gesture "" to stop the AI tracking (Indicator light turns red).
5. AI tracking for front/rear camera: For front camera tracking, align the magnetic AI vision sensor with the phone screen. Place the vision sensor in the opposite direction for rear camera tracking.



It is completely normal for the magnetic alignment to become hot when the fill light is in use and hence, it is advisable NOT to make a direct contact with the hot alignment, especially the metallic part.

*** FAQ: How to make AI vision positioning adjustments? (Customized Composition)**

If the framed subject cannot be centered on the phone screen, or you want to customize the AI vision position to be tracked:

1. Make sure the gimbal & AI vision sensors are on.
2. Take the gesture " " towards the AI vision sensor and and the indicator light will quickly blink in green color.
3. Move in front of the screen until you find the preferred position to be tracked.
4. Show the gesture " "to lock the position and create the ideal composition (the indicator light will stop flashing).

07 How to Use the Gimbal

On-board Features

Power button

Press and hold for 3 seconds: Power on/off

* When Powered On
Press twice: Enter the standby mode

Press once: Wake up the gimbal



M button

Press once: Switch between gimbal modes (PF-PTF-L-POV)

Press three times: "ICP" Inception mode/360° infinite spin shot
(Press the trigger twice to recenter the gimbal).

Press five times: Auto calibration

Press seven times: Remote control pairing

Press nine times: Clear the paired remote control



Joystick

Push the joystick up & down: Tilt rotation control

Push the joystick left & right: Pan rotation control



Trigger

Press on: Sport mode "S"

Press twice: Recenter the gimbal

Press three times: Reverse 180° panning rotation

Press four times: Ultra-wide-angle shot mode

After a quick short press, press and hold: Quick switch to All Lock Mode(Switch back to the previous gimbal mode after releasing the trigger.)



Zoom lever

Lever up/down: Zoom in/out (T/W)
(Requires to be used with Hohem Joy.)

Shutter button

Half-press: Focus (Requires to be used with Hohem Joy.)

Press once: Take a photo; Start/end video (Please ensure the Bluetooth pairing.)

Press twice: Photo/video switch (Only available in the Hohem Joy app or on the native camera app of certain standard protocol phones with Android 10.0 or later versions. Please ensure Bluetooth is connected.)

Press three times: Front/rear camera switch (Only available in the Hohem Joy app or on the native camera app of certain standard protocol phones with Android 10.0 or later versions. Please ensure Bluetooth is connected.)



Multifunctional control wheel

Press twice: Focus/Roll switch

Focus: Focus control (Only available in the Hohem Joy.)

Roll rotation: +/-45°

Press three times: CCT/RGB switch

CCT: Adjust color temperature and brightness of cold/warm light.

RGB: Control color and brightness of RGB light

Press and hold: Turn on/off CCT fill light or RGB light (Among the 4 modes above, "ON"/"OFF" occurs only in CCT/RGB mode.)

Press once: Select option (Only available for CCT/RGB mode.)

Buttons for A-B motion

Button A/B is used to set the start/end point when capturing shots of specific tracks, or making motion timelapse in various APPs ie camera APPs (Note: Motion timelapse in Hohem Joy APP can’t be used at the same time).

Setting position A: Move the camera angle with the joystick to the start point, position A and long press Button A to set. A short beep means successful setting.

Setting position B: Move the camera angle with the joystick to the end point, position B and long press Button B to set. A short beep means successful setting.

A-B motion: Single press button A to return to position A from the current position, and then double press Button B to start A-B motion at a constant speed.

B-A motion: Single press button B to return to position B from the current position, and then double press Button A to start B-A motion at a constant speed.

*Duration by default: 1 minute. You can customize duration in the Hohem Joy APP (Tap Settings icon - Gimbal Stabilizer Settings - Duration to select the required duration)

Modes Description



Pan Follow (PF):
Tilt & roll axis both are locked, and camera is able to move to left or right smoothly.



Pan & Tilt Follow (PTF):
Roll axis is locked, and camera is able to move to left/right, and tilt up/down.



All Lock (L):
Camera stays in its current orientation.



All Follow (POV):
Also known as first-person shot. Tilt axis, roll axis and pan axis all follow the movement of the gimbal.



Sport Mode (S):
The follow speed of the gimbal increases for capturing quick-moving subjects and any fast paced action.



Inception (ICP):
360° infinite spinning on pan axis while holding the gimbal horizontally.

Manual Tilt Adjustment



Manual Tilt Adjustment

The tilt motor can be rotated by a certain angle by hand. Hold it for 2s and the camera angle will be fixed at that angle.

08 OLED Display

Front Page

1. Wheel Working Status

ROLL	Roll Axis Rotation
FOCUS	Focus Control
CCT ON ▸100% 6000K	Fill Light ▸100% Brightness 6000K Color Temperature
RGB ON ▸360° 100%	RGB Light Brightness 100% Brightness ▸360° Hue

2. Current Mode

PF	Pan Follow	PTF	Pan & Tilt Follow
L	All Lock	POV	All Follow
S	Sport	ICP	Inception

3. Bluetooth: Connected; Disconnected

4. Battery Level: Current Level Charging

Low Battery

5. Standby: SLEEP Gimbal enters standby mode

6. Pan Axis Latch: UNLOCK THE LATCH Unlock the Latch

7. Error: ERROR Using gimbal before unlocking roll axis lock pin or pan axis latch, overload warning, or motor error due to improper installation/operation.

8. A-B Motion: A Move to the point A from the current point at a constant speed

B Move to the point B from the current point at a constant speed

9. Auto Calibration: CALIBRATING··· Calibrating

10. Firmware Update: UPDATING··· Updating

11. Pair Remote Control (Excluded): PAIRING··· Pairing

PAIRED Paired Successfully PAIRING FAILED Pairing Failed

09 How to Use the APP

How to Connect

1. Power on iSteady M6
2. Turn on Bluetooth on the Mobile Phone
3. Launch the app Hohem Joy and follow the prompts to connect iSteady M6 device.

***Gimbal connection troubleshooting: If the gimbal device cannot be searched or has been paired with another mobile phone, please delete all the Bluetooth information and try to pair again.**

Long-pressing the M button for five seconds while simultaneously pushing up on the Zoom lever. If the Bluetooth symbol on the display changes to " ", it implies that the paired device has been cleared. If you want to add another device, just repeat the procedures above.



APP Features



1. Switch between front camera and rear camera.
2. Smart Tracking: Auto face/framed object tracking
3. Settings: To set parameters for gimbal and camera and to check out available firmware updates.
4. Beauty & Filters
5. Gesture Control: Gesture" " to enable countdown PHOTO/VIDEO. Gesture " " to stop it.
6. Moment mode: On-tap blockbuster with diverse templates in the Moment mode.
7. Focus/Zoom in or out

* For more details on the "Hohem Joy" app features, please visit the official website of HOHEM (www.hohem.com) and watch iSteady M6 video tutorials.

Hohem Joy

10 Auto Calibration and Firmware Update

Calibration Reasons and How to Calibrate

Auto calibration could reduce drift or slight deviation caused by nearby magnetic interference or human error.

Calibration failure might happen if the gimbal is not placed on a flat surface for calibration (e.g. calibration in a running vehicle).

❶

Place gimbal on a flat surface by means of a tripod.



❷

Double press the trigger to recenter the gimbal.



❸

Press the M button five times to enable the auto calibration and you will hear a beep sound. Please do not touch the gimbal during calibration.



❹

The second beep indicates that the calibration is completed, and the gimbal will be recentered automatically.



*Two short beeps, following the calibration failure, indicates that the gimbal has been in the standby mode. Single press Power button can wake up the gimbal. Then, follow the steps above to re-calibrate.

Firmware Update

You will be prompted in the app Hohem Joy if a new firmware update is available. Follow the on-screen instructions in the app to update the firmware.

11 Specifications

Weight (Gimbal)	551g (Including battery)
Main Material	High-Performance Composites
Payload	400g
Mobile Width	58mm~98mm
Battery Capacity	2600mAh 7.4V / 19.24Wh
Battery Life	Up to 18 hours (Under ideal conditions with the gimbal fully balanced) 6-8 hours (Use AI tracking and fill light at its highest brightness) *HOHEM lab test results
Charging Time	3 Hours（5V⎓2A）
Mechanical Range	Pan: 360° Infinite Rotation Roll: 335° Tilt: 335°
Working Temperature	-10~45° C
Motors Protection	The motor can be protected from damage caused by improper operation by having the gimbal powered off automatically.

12 Disclaimer

・ Thank you for purchasing iSteady M6. By using this product, you hereby signify that you have read this document carefully and that you understand and agree to abide by the terms and conditions herein. You agree that you are solely responsible for your own conduct while using this product, and for any consequences thereof. You agree to use this product only for purposes that are proper and in accordance with all terms, policies and guidelines HOHEM has made and may make available.

・ HOHEM accepts no liability for damage, injury or any legal responsibility incurred directly or indirectly from the use of this product. Users shall observe safe operation guidelines including, but not limited to, those set forth herein.

・ HOHEM reserves all rights for final explanation on this instruction and other documents related to iSteady M6. The information is subject to update without notice. Please visit www.hohem.com to obtain the latest product information.

hohem

Hohem Technology Co., Ltd.

Email: service@hohem.com
Website: www.hohem.com
Manufacturer: Hohem Technology Co., Ltd

Connect us at Facebook

13 Warranty Terms

① Customers are entitled to replacement service in case of quality deficits or functional disorders found in the product within seven (7) to thirty (30) calendar days of receiving the product, subject to the policy of the actual sales platform.

② The official warranty period is 12 months (1 year) counting from the date of selling under normal use. The actual warranty coverage is subject to applicable local laws and regulations in the region where the product is sold, as well as the specific warranty policies of the sales platform. Accessories are excluded from warranty service. The warranty service is subject to normal use. Damage exceeding this period, or damage caused by force majeure, is not covered by warranty. This includes damages not related to the product' s quality such as collisions, burns, unauthorized repairs or modifications, foreign objects (water, oil, sand, etc.), and damages resulting from improper installation or use. Our company can offer paid repair services for such issues.

③ Please keep and provide the warranty card or an equivalent proof of purchase when requesting warranty service.

CALL CENTER -Toll Free

UNITED STATES:

+1(888)9658512 Mon-Fri: 9:00AM-5:00PM (EST)

UNITED KINGDOM:

+44(0)808 2737578 Mon-Fri: 2:00PM-10:00PM (GMT +0)

CANADA:

+1(855)758-8939 Mon-Fri: 9:00AM-5:00PM (EST)

BRAZIL:

+55 (0)800 5911897 Mon-Fri: 10:00AM-6:00PM (GMT -3)

Warranty Card

User Name:

Contact No.:

Address:

Purchase Date:

Prod. Serial No.:

Failure Cause:

Service Record: